

Polaroid Everest 3.20 UV Hybrid

Head Option

Ricoh G6 5 Pl. / Kyocera 5 Pl. (Optional)

Printing Speed

12 Heads Ricoh G6 CMYK + W

Production	High Quality	Ultra Quality
115 sqm2/h	75 sqm2/h	45 sqm2/h
1237 sqf2/h	807 sqf2/h	484 sqf2/h

12 Heads Kyocera CMYK + W

Production	High Quality	Ultra Quality
145 sqm2/h	90 sqm2/h	60 sqm2/h
1560 sqf2/h	968 sqf2/h	645 sqf2/h



Curing System	UV LED
Ricoh G6 / Kyocera	From 4 up to 12 printheads
Color Option	C M Y K + White + Varnish (Optional)
Printing Mode	Unidirectional / Bi-directional
Media Thickness	4 inches
Rip	Photo Print
Resolution	1200 DPI
Ink Type	UV LED
Media	Glass, Acrylic, Wood, PVC, Metal Panels, Ceramic Tiles, KT board WPC, MDF, Ceiling Film, Vinyl, Advertising Banner, PET, Wall paper and so on
Power Supply	220v 5500w
Operation Conditions	Temperature 20°C - 28°C / 68°F - 74°F Relative Humidity 40% to 60%
Printer Dimensions	18.67x5.46x5.32 ft / 5692x1665x1623mm
Packaging Dimensions	19.02x7.21x5.90 ft / 5800x2200x1800mm
Recommended Placement Area	21.32x16.40 ft / 6500x5000mm

*Images, features and specifications are illustrative and may vary or change without prior notice.

