

Polaroid T-Rex FBS 2.44x1.22m UV

Head Option
Ricoh G6 5 PL

Printing Speed

Production Mode	High Quality	Ultra Quality
50 m2/h 538 sqf/h	35 m2/h 376 sqf/h	25 m2/h 269 sqf/h



Curing System	UV LED Curable Ink
Ricoh G6	From 2 up to 8 print heads
Color Option	C M Y K + W + Varnish (Optional)
Printing Mode	Unidirectional / Bi-directional
Media Thickness	4 inches
Rip	Photo Print
Resolution	1200 DPI
Ink Type	UV LED
Media	Glass, Acrylic, Wood, PVC, Metal Panels, Ceramic Tiles, KT board WPC, MDF, Ceiling Film, Vinyl, Advertising Banner, PET, Wall paper and so on
Power Supply	220v 5500w
Operation Conditions	Temperature 20°C - 28°C / 68°F - 74°F Relative Humidity 40% to 60%
Printer Dimensions	13.51 x 7.08 x 4.92 ft / 4120 x 2160 x 1500mm
Packaging Dimensions	16.68 x 7.25 x 5.08 ft / 4170 x 2210 x 1550mm
Recommended Placement Area	19.68 x 11.48 ft / 6000 x 3500mm

*Images, features and specifications are illustrative and may vary or change without prior notice.

